

Scheda Prodotto

**COD: CT1469344****CT1469344**

REIFENHAUSER

IMPIANTO FILM

USATO/A

ANNO: 2003

COLORE: GRIGIO

Number of Layers: 3

Film structure: ABC

Material: LDPE, LLDPE, MDPE Others Blends

Film width (mm): 2300

Output (kg/h): 400

Extruder 1 Layer ref: A

Screw diam 1 (mm): 60

Description: AC motor 60 kw, Gravimetric dosing Doteco 5 components

Extruder 2 Layer ref: B

Screw diam 2 (mm): 80

Description: AC motor 117 kw, Gravimetric dosing Doteco 5 components

Extruder 3 Layer ref: C

Screw diam 1 (mm): 60

Description: AC motor 60 kw, Gravimetric dosing Doteco 5 components

Head description: coex3, rotating, IBC, Ultrasonic diam sensor

Die diam (mm): 400 + 280

Thickness controll system: Automatic thickness profile control

Bubble cage: Motorized

Panel for gussets: Yes

Take off unit: oscillating take off unit Reinhold 2300 with gusseting panels

Corona treatment: MERO

Web guide: Erhard+Leimer

Rewinder Type: Double back to back

Rewinder max reel diameter: 1000

Rewinder description: Model UFA 01A1

Additional Information: Edge trim, shredding Exact and Recovery regrulator Macchi, Recotrim Chiller, Eurochiller